

Serie chiodatrice (DOP) (Series)	modello	misure impiegabili (mm)	capacità caricatore (n.punti)	pressione (kg/cm ²)	peso (kg)	consumo aria (litri/colpo)	dimensioni (mm - L x W x H)
	model	applicable sizes (inch)	magazine capacity (pieces)	pressure (PSI)	weight (lbs)	air consumption (ltr/cycle)	dimensions (inch - L x W x H)

GRAFFE PESANTI HEAVY WIRE STAPLES

M2



M2.38 B

420	M2.38 B	15 ÷ 40	80	5 ÷ 7,5	1,50	0,54	242 x 58 x 245
		5/8" ÷ 1-9/16"	80	70 ÷ 105	3,30	0,01906	9-1/2" x 2-5/16" x 9-5/8"

UTILIZZI APPLICATIONS

Coperture, sotto-pavimentazione, impermeabilizzazione tetti, rivestimenti, produzione finestre e cinte, intelaiatura mobili (fusti per salotti), assemblaggio mobili e mobiletti, costruzione di casse, scatole e insegne, imballaggi in legno, riparazione bancali, basamenti, finiture interne in legno.

Sheathing, subflooring, roof decking, furring, production of window units and fencing, furniture frames (living-room furniture frames), cabinets/ furniture assembling, crates, boxes and shingles manufacturing, wooden packaging, pallets repair, underlayment, trimming.



M2.740 NS



Versione NO-SAG
NO-SAG model

740	M2.740 NS	15 ÷ 40	145	5 ÷ 7,5	1,70	0,75	340 x 77 x 256
		5/8" ÷ 1-9/16"	145	70 ÷ 105	3,75	0,0264	13-3/8" x 3-1/16" x 10-1/16"
	M2.740 NO-SAG	15 ÷ 40	145	5 ÷ 7,5	1,70	0,75	340 x 77 x 258
		5/8" ÷ 1-9/16"	145	70 ÷ 105	3,75	0,0264	13-3/8" x 3-1/16" x 10-3/16"

SPECIFICHE SPECIFICATIONS

Punti per barretta 71
Staples per strip 71

Finitura lucido
Finishing bright

A richiesta zincato, inox, punta DP, punta DPP, certificazione CE 14592

On request galvanized, stainless steel, DP point, DPP point, CE 14592 Certification



M2.65



M2.50

840	M2.65	20 ÷ 65	145	5 ÷ 7,5	2,14	1,40	355 x 98 x 290
		3/4" ÷ 2-9/16"	145	70 ÷ 105	4,72	0,0494	14" x 3-7/8" x 11-3/4"
850	M2.50	20 ÷ 50	145	5 ÷ 7,5	2,24	1,22	352 x 91 x 263
		3/4" ÷ 2"	145	70 ÷ 105	4,94	0,04308	13-7/8" x 3-9/16" x 10-3/8"

